


# N'RUN 5S EVO







## N'RUN 5S





#### General Specifications

MOTORS

1 engine height (6000 N)

1 motor middle section (6000 N)

HEIGHT ADJUSTMENT

-/+ 59/95 cm

WEIGHT

152,5 kg

LIFTING CAPACITY 250 kg

POWER SUPPLY

AC100 - 120V, 50/60 Hz

AC220 - 240V, 50/60 Hz

INSULATION CLASS

Reinforced insulation II

PRODUCT CLASSIFICATION

Class I Equipment

APPLIED PARTS

Type B

MOISTURE RESISTANCE

IPX0

CONFORMITY

IEC 60601-1:2005, IEC 60601-1:2005/AMD1:2012

EN 60601-1-2:2015, IEC 60601-1-6:2010

IEC 60601-1-6:2010/AMD1:2013, ISO 10993-10:2010

ISO 10993-5:2009

FRAME COLOUR

RAL 7047 + RAL 7011

FEEDER CABLE

3m, White

## Upholstery

7cm

Wood base  $1,5 \text{ cm} + 4 \text{ cm} 120 \text{kg/m}^3 + 1,5 \text{ cm} 40 \text{kg/m}^3$ 

Upholstery with straight edges and finished with a saddle stitch.

Coating: 100% vinyl. Permablok 3 © advanced vinyl protection (against germs and bacteria). Superior abrasion resistance: >300K cycles.

Flame retardancy: NF P 92-503/M2



Colour: Graphite

## Operation

TwinLift  $\circledR$  arm supports: stepless and simultaneously adjustable with gas spring. No collision with the therapist.

Head section with 2 gas springs.

B'Soft headrest: high-tech headsection and nosepin in single density foam. Seamless and soft.

Fully integrated peripheral switch, easy access from all sides of the table.

Heating: Cushion heating with XL heating elements.

Foldable Side wings.

4 wheels turning  $360^{\circ}$ . Fully integrated system underneath the base frame. 2 levers lift the table on its 4 wheels.

Electrically adjustable middle section. Switches on both sides.

Foot section with 1 gas spring. White LED light in the under carriage

### Safety

Safety switch with key (power off).

Double tip system with automatic standby system (5 sec), for all motors.

#### Warranty

2 years on table and upholstery.

#### Accessories

3 models of stools, 5 colours



#### Paper roll holder



#### Bed covers, 2 colours

